EFVS-450

Flamingo Vibratory Sieve

Designed for generic separation, the LS basic model is suitable for wet/dry, grading, classification, dedusting, and quality control. The multi-purpose model is essential to improve quality and safety of production materials, increase productivity, and reduce cost and labour.

Continuous development along with various available add-ons, makes the LS basic model a versatile unit capable of separation up to 6 grades (5 screens).

Features:

- Simple and functional design higher capacity, easy use, less maintenance, lower noise, and requires minimal floor space.
- Lower energy consumption reduce cost.
- Simple and functional design higher capacity, easy use, less maintenance, lower noise, and require minimal floor space.

- Lower energy consumption- reduce cost.
- Light weight- easily movable with pellet jack or forklift.
- Highly durable- designed for long hours of operation with minimal service required.
- Anti-binding devices prevent screen clog without creating dust clouds during operations.
- Automatic discharge of separated materials continuous and uninterrupted production.
- Up to 5 screens per unit- allowing multiple separations with just one unit for cost effective operation.
- Quick change design- allows fine screen change in less than 5 minutes.

Stainless Steel- all contact parts in stainless steel SS304. Full or partial SS316L upgrades available.

Wide range of sizes and modifications available to suit all types of powder and liquids.





MODEL#		# OF	POWER	DIAMETER	DIMENSION	WEIGHT (KG)
		SCREEN		OF SCREEN	(L X W X H, MM)	
		DECK		SURFACE		
EFVS-300		1	1/6HP	300mm	320 x 350 x 520	20
EFVS-450			1/2HP		500 x 500 x 660	40
EFVS-600	-1S	1	3/4 HP	540mm	770 x 770 x 830	95
	-2S	2			770 x 770 x 940	120
	-3S	3			770 x 770 x 1130	145
EFVS-800	-1S	1	1 HP	740mm	930 x 1000 x 950	145
	-2S	2			930 x 1000 x 1090	177
	-3S	3			1040 x 1040 x 1250	210
EFVS-1000	-15	1	2 HP	910mm	1150 x 1150 x 1020	211
	-2S	2			1170 x 1170 x 1200	265
	-3S	3			1190 x 1190 x 1330	320
EFVS-1200	-15	1	2 HP	1110mm	1310 x 1410 x 1190	313
	-2S	2			1310 x 1410 x 1350	380
	-3S	3			1350 x 1350 x 1510	447
EFVS-1500	-1S	1	3 HP	1410mm	1610 x 1670 x 1270	497
	-2S	2			1650 x 1650 x 1470	580
	-3S	3			1650 x 1650 x 1700	665



EFVS-450-SAN



^{*} Please confirm specifications on order as features may change