



Flamingo C Series Hammer Mills

Flamingo C-Series EFHM-C hammer mills are suitable for Lump Breaking, Granulating, Pulping & Size, Reduction of material such as Chemical, Food, Fruit & Vegetables, Clay, Resins and Grains. Hammer Mills are also used for Recycling Bread, biscuits and compacting waste. Swing or Fixed design Hammers

Features:

- Stainless Steel contact parts (Grade 304)
- Quick Interchangeable Screens
- Bottom Discharge for Easy Bagging Off
- Easy Cleaning
- Large Feed Openings with Feed Gate
- Heavy Duty Ball Bearing Rotors
- Taper Lock Pulleys (standard)
- Fitted with Work Cover approved Safety Switch
- 415 volt 3 phase (standard) / 240 volt 1 phase (C7 optional)
- Capacities to 1500kg/hr, 4mm screen (product dependant)


Options:

- Stand
- Fixed Blades C-Series Hammer Mills
- Special Motors and variable speed drives
- Grade 316 Stainless Steel.
- Special designs made to order Hammers of special materials
- Electrical wiring, E-Stop, plug & contactor can be supplied
- Screen from 0.5- 25mm

A-Series Hammer Mills are heavy duty for difficult and high production requirements.

Capacities to 5 tonnes/hr, 4mm screen (product dependant))

EFHM-C18



Specifications

| | | |
|----------------|---------|---------------|
| Capacity | Kg/hr | 1500 |
| Rotor Speed | rpm | 2800 |
| Chamber Size | mm | 500 dia x 450 |
| Feed Opening | mm | 450 x 250 |
| Machine Power | kW (hp) | 18.5 (25) |
| Overall Height | mm | 1400 |
| Overall Length | mm | 2100 |
| Overall Width | mm | 660 |
| Overall Weight | Kg | 340 |

* Please confirm specifications on order as features may change