



since 1946

Ernest Fleming
machinery & equipment pty ltd

Website: www.fleming.com.au

Phone: (+61) 02 9427 3270

Email: sales@fleming.com.au

Address: 7/27 Mars Rd, Lane Cove West, Sydney NSW 2066 Australia

Flamingo C Series Hammer Mills

Flamingo C-Series EFHM-C hammer mills are suitable for Lump Breaking, Granulating, Pulping & Size, Reduction of material such as Chemical, Food, Fruit & Vegetables, Clay, Resins and Grains. Hammer Mills are also used for Recycling Bread, biscuits and compacting waste. Swing or Fixed design Hammers

Features:

- Stainless Steel contact parts (Grade 304)
- Quick Interchangeable Screens
- Bottom Discharge for Easy Bagging Off
- Easy Cleaning
- Large Feed Openings with Feed Gate
- Heavy Duty Ball Bearing Rotors
- Taper Lock Pulleys (standard)
- Fitted with Work Cover approved Safety Switch
- 415 volt 3 phase (standard) / 240 volt 1 phase (C7 optional)
- Capacities to 1500kg/hr, 4mm screen (product dependant)


Options:

- Stand
- Fixed Blades C-Series Hammer Mills
- Special Motors and variable speed drives
- Grade 316 Stainless Steel.
- Special designs made to order Hammers of special materials
- Electrical wiring, E-Stop, plug & contactor can be supplied
- Screen from 0.5- 25mm

A-Series Hammer Mills are heavy duty for difficult and high production requirements.

Capacities to 5 tonnes/hr, 4mm screen (product dependant))

EFHM-C12



Specifications

Capacity	Kg/hr	1000
Rotor Speed	rpm	2800
Chamber Size	mm	250 dia x 300
Feed Opening	mm	300 x 125
Machine Power	kW (hp)	4.0 (5.5)
Overall Height	mm	900
Overall Length	mm	1600
Overall Width	mm	660
Overall Weight	Kg	123

* Please confirm specifications on order as features may change